

Low alloy steels

Part 2

Stooss specification	DIN material no.	Short specification according to DIN	EN specification	GB	USA Type	UNS	F	J	Chemical analysis in weight per cent								Upper and lower range												
									C	Si	Mn	P	S	Cr	Ni	Mo	V	Al	Nb	Other									
<b>Low alloy tempering steels</b>																													
<b>23 CrNiMo 7 47</b>	1.6749	23 CrNiMo 7 47			ASTM A471	K32800			min. 0.20	0.50			1.70	0.90	0.60														
			SEW 555 / Turbine and generator construction / Hub and cover disks						max. 0.25	0.30	0.80	0.010	0.015	2.00	1.20	0.80	0.05	0.025								Cu max. 0.20			
<b>30 CrNiMo 8</b>	1.6580HH	30 CrNiMo 8 HH	30 CrNiMo 8	823M30		30CND8	SNC M1		min. 0.30	0.15	0.50			1.80	1.80	0.30											Sn max. 0.025 Cu max. 0.20		
			DIN 17201 / SEW 550 / EN 10083-1 / Machine and equipment construction						max. 0.34	0.40	0.80	0.015	0.007	2.20	2.20	0.50													
<b>31 CrMoV 9</b>	1.8519	31 CrMoV 9							min. 0.28	0.15	0.40			2.30		0.15	0.10										Sn max. 0.010 Cu max. 0.20		
			DIN 17211 / Nitride steel / crankshafts, valve spindles						max. 0.34	0.40	0.70	0.009	0.007	2.70		0.25	0.20												
<b>34 CrAlNi 7</b>	1.8550	34 CrAlNi 7			ASTM A355	K52440			min. 0.30	0.15	0.40			1.50	0.90	0.15		0.80											
			DIN 17211 / Nitride steel / piston rods, spindles						max. 0.37	0.35	0.60	0.025	0.025	1.80	1.10	0.25		1.10											
<b>56 NiCrMoV 7</b>	1.2714	56 NiCrMoV 7	35CrMo8						min. 0.50	0.10	0.65			1.00	1.50	0.45	0.07	0.008											
			DIN 17350 / Tool steel / tools for hot work / forging dies						max. 0.60	0.40	0.95	0.030	0.030	1.20	1.80	0.55	0.12	0.020								Cu+10Sn max. 0.50			
<b>40 NiCrMo 6</b>	1.6565	40 NiCrMo 6	818M40	AISI 4340				SNC M8	min. 0.36	0.15	0.50			1.00	1.40	0.20													
			Tool steel / dies for briquetting and compacting equipment						max. 0.44	0.35	0.70	0.025	0.025	1.40	1.70	0.30													
<b>15 Mo 3</b>	1.5415	15 Mo 3	16Mo3	243B		K11820	15D3	STBA 12	min. 0.12	0.15	0.50							0.25											
			DIN 17243 / EN 10028 / High temperature steel / application temperature up to max. 500°C. / power station construction / flanges						max. 0.20	0.35	0.70	0.035	0.030	0.25	0.30	0.35		0.050											
<b>22 Mo 4</b>	1.5419	22 Mo 4	G20Mo5	245	SAE 4422			SCPH 11	min. 0.18	0.20	0.40						0.30												
			DIN 17245 / EN 10213-2 / High temperature steel / application temperature up to max. 500°C. / power station construction / flanges						max. 0.25	0.40	0.70	0.015	0.018	0.30		0.50													
<b>20 CrMoNiV 47</b>	1.6979	20 CrMoNiV 47							min. 0.17	0.30				1.20	0.50	0.80	0.25												
			SEW 555 / Turbine construction and generator devices						max. 0.25	0.30	0.50	0.015	0.018	1.40	0.60	1.00	0.35	0.020											
<b>13 CrMo 4 4</b>	1.7335	13 CrMo 4 4	13CrMo4-5	620		K11562	15CD4-05	STBA 20	min. 0.10	0.10	0.40			0.80		0.45													
			DIN 17243 / EN 10028-2 / High temperature steel / application temperature up to max. 530°C. / power station construction						max. 0.18	0.35	0.70	0.025	0.015	1.10	0.30	0.60		0.030											
<b>10 CrMo 9 10</b>	1.7380	10 CrMo 9 10	10CrMo9-10	622		K21390	12CD9-10	STBA 24	min. 0.10	0.15	0.40			2.00		0.90		0.010									Cu max. 0.25 N max. 0.012		
			DIN 17243 / EN 10028 / SEW 595 / High temperature steel / application temperature up to max. 500°C. / power station construction						max. 0.14	0.30	0.60	0.015	0.010	2.50		1.10		0.040											
<b>3520</b>	1.3520	100 CrMn 6	100CrMn6			K19195	100CM6		min. 0.90	0.55	1.05			1.45			0.005		Ti max. 0.003 Cu max. 0.25										
			DIN 17230 / Roller bearing steel / WD to 50 mm						max. 1.00	0.70	1.20	0.025	0.008	1.65	0.30	0.80		0.050	O max. 0.0015										
<b>3539</b>	1.3539	100 CrMnMo 8					100CrMnMo8		min. 0.90	0.40	0.80			1.80		0.50		0.015		Ti max. 0.003 Cu max. 0.25									
			DIN 17230 / Roller bearing steel / WD > 50 mm						max. 1.00	0.60	1.10	0.025	0.008	2.05	0.30	0.60		0.050	O max. 0.0015										
<b>3536</b>	1.3536	100 CrMo 7 3	100CrMnMo7		ASTM A485		100CrMo7-3		min. 0.90	0.20	0.60			1.65		0.20		0.015		Ti max. 0.003 Cu max. 0.25									
			DIN 17230 / Roller bearing steel / WD > 50 mm						max. 1.00	0.40	0.80	0.025	0.008	1.95	0.30	0.35		0.050	O max. 0.0015										
<b>100 Cr 6</b>	1.3505	100 Cr 6	100Cr6	2S.135	SAE 52100		100C6	SUJ 2	min. 0.98	0.20	0.25			1.40													Cu max. 0.30		
			DIN 17230 / Roller bearing steel / WD up to 30 mm						max. 1.05	0.30	0.45	0.025	0.025	1.60	0.30														
<b>100 Cr 6 M1</b>	1.3505	100 Cr 6	Modified Analysis						min. 0.90	0.20	0.30			1.45			0.010	Cu	As max. 0.04 Sn max. 0.03 Ti max. 0.003										
			DIN 17230 / Roller bearing steel / WD up to 30 mm						max. 1.00	0.35	0.45	0.025	0.008	1.65	0.25	0.80		0.050	O max. 0.0015 Sb max. 0.005 Pb max. 0.002										
<b>65 Cr 3</b>	1.7017	65 Cr 3							min. 0.63	0.25	0.55</td																		